


DIN13




AL-CU-FE

ALLUMINIO, RAME, FERRO - ALUMINIUM, COPPER, IRON - ALUMINIUM, CUIVRE, FER

DIN 371
d1 ≤ M10



DIN 376
d1 ≥ M12



Profondità di filettatura - Thread depth - Prof. de filetage	3xD	3xD	
Materiale - Tool Material - Substrat	HSSE	HSSE	
Tolleranza - Thread tolerance - Tolérance du filetage	ISO2/6H	ISO2/6H	
Trattamento superficiale - Surface treatment - Revêtement		TXC	

DIN 371	Ød1 M	P mm	L ₁	L ₂	d ₂ h9	a h12	Z	
3	0,5	56	10	3,5	2,7	3	2,5	
4	0,7	63	13	4,5	3,4	3	3,3	
4,5	0,75	70	13	6	4,9	3	3,7	
5	0,8	70	13	6	4,9	3	4,2	
6	1	80	16	6	4,9	3	5	
8	1,25	90	18	8	6,2	3	6,8	
10	1,5	100	20	10	8	3	8,5	

CODE			
E24M3AZ	E24M3AZ-TXC		
E24M4AZ	E24M4AZ-TXC		
E24M4,5AZ	E24M4,5AZ-TXC		
E24M5AZ	E24M5AZ-TXC		
E24M6AZ	E24M6AZ-TXC		
E24M8AZ	E24M8AZ-TXC		
E24M10AZ	E24M10AZ-TXC		

DIN 376	Ød1 M	P mm	L ₁	L ₂	d ₂ h9	a h12	Z	
12	1,75	110	25	9	7	3	10,3	
14	2	110	28	11	9	3	12	
16	2	110	28	12	9	3	14	

CODE			
E25M12AZ	E25M12AZ-TXC		
E25M14AZ	E25M14AZ-TXC		
E25M16AZ	E25M16AZ-TXC		

ISO	Campo di impiego Application range Gamme d'application	Gruppo di materiali - Velocità di taglio m/min Material groups - Cutting speed m/min Groupes de matières - Vitesse de coupe m/min									
P	Acciaio - Steel - Acier - Rm ≤ 700 N/mm²	●1.1 10-15	●1.2 10-15			●1.1 20-30	●1.2 20-30				
N	Leghe di Alluminio - Al alloys - Alliage Al Truciolo lungo - Long chipping - Copeaux longs	●4.1 10-15	●4.2 15-20			●4.1 20-25	●4.2 25-30				
N	Leghe di Rame - Copper alloys - Alliages de cuivre	●5.1 8-12	●5.2 10-15			●5.1 15-20	●5.2 20-25				
S	Titanio puro - Pure titanium - Titane pur	●6.1 5-8									
S	Nichel puro - Pure nickel - Nickel pure	●7.1 6-8									
N	Materiali termoplastici – Thermoplastics - Thermoplastiques Truciolo lungo – Long chipping - Copeaux longue	●8.1 20-25									